

Quality Assurance System 质保体系

OEM&ODM GAS BOILER Zhongshan Calorie Heat Energy Technological Co.1

专业权威认证

经过多年建设和不断完善,我们的质量保证体系植根于从产品设计到客户服务的每一个环节,无论是技术专家,还是兢兢 业业的一线工人,都深知其中的含义,强烈的精品意识和严格的过程管理使我们的生产流程符合ISO9001国际质量管理体系认 证,保证了每一台产品的品质都达到尽善尽美。

After great efforts for many years and our keep improving spirit, our quality assurance system is built in all of our employees in each procedures, e.g. Design, production, service, etc. And No matter he is a technicians or assembling worker, all of them are well unde rstood the quality/ideology. Strong ideology of precise product and strict process managementguarantee, ensured our company are ISO9001 authorized. Also assuredeach of our product is with perfect quality.









自主研发生产壁挂炉核心部件—主控器

四合一壁挂炉主控制器维修更方便 Combined controller, convenient for after sold

套管式/板换式/套管烟道/板换烟道

ue bithermal / flue monothermal









省气・省电・高科技 节能壁挂炉

Show The Product With Science And Technology Make The Brand With Speciality

生产体系

完美的生产过程,不仅仅在于我们拥有先进的生产工艺设备和完善的绘测手段,相比之下,我们更注重人在此过程中起的关键作 用,技术专家和专业技术人员的全程参与,使得我们的产品在制造过程中就具备了优异的品质和潜在的价值,亦使卡洛力品牌更多 了一份务实的内涵。

Perfect production system does not only mean that we have advanced technics, production equipment, and perfect inspection instruments, but also we pay more attention to the people who act as the key function in production. Meanwhile the experts and technicians also take part in all procedures, so out products are all with excellent quality and potential values, Also Calorie brand owns good reputation in the market.









专业铸就品质,实力创造辉煌

自主研发拥有知识产权的控制器

Develop and produce boiler main controller

专业制造壁挂炉主控器

Professional on boiler controlled production.

供暖负荷自动调节

Heating load auto controlled

节能省气功能 Energy-efficient function

故障自动检索·人性化操作 Error auto display, humanized control

新旧主控器兼容性强大

New and old master controllers have strong compatibility






> Enamel tank water tank 搪瓷内胆水箱

搪瓷内胆水箱

主要特点

- 1、内胆; 采用目前高档电热水器产品选用的搪瓷内胆, 宝钢搪瓷专用钢板为基材。
- 2、換熱夹层:采用夹层结构换热,换热面积0.65平方米,换热效率更高,耐压达0.6MPa, 品质卓越,寿命长。
- 3、优质不锈钢加热管,加热效率高达97.9%;强力阳极棒,更有效妨腐防垢,达到国家 A级标准。
- 4、采用加厚无氟聚氨酯发泡隔热层,高效保温,减少热损失。
- 5、循环性能好,独特的管套低水位进水设计,平稳改变进水方向,使冷水有序积沉在水箱 底部,有效减少冷热水的不合理混合、使热水出水率提高60%以上,保证热水持续不断。
- 6、內置中央智能控制系统:具有温差循环、过热保护、定时加热、压力限定等功能,实现 智能化控制,使用安全、便利,每天畅享热水。





水箱参数

方式	容量(L)	外形尺寸Φ(mm)	换热方式	夹层换热面积(m²)
力主父正	80/100/120	450×1060 470×1100 470×1270	介质换热	0.65-0.9
内胆	内胆处理	夹层	外壳	保温层
18m空间10-34R超空雨	到海绵孙-波-308 33	1.5mmSPCC碳钢板	0.45mm镀锌板喷塑	45mm聚氨脂酸体保温

额定压力(MP)	介质运行压力(MP)	最大承压(MP)	换热器	电加热功率
0.7	0.2	1.5	英格莱300不把卵毛加热棒	1.5KW
毛重	进出水口尺寸	传感器接口	外观颜色	制造标准
40-50kg	453	4分	白色带丝网印刷	G84706.1-2005



















省气・省电・高科技

The Product With Science And Techn Make The Brand With Speciality 节能壁挂炉

中山市卡洛力热能科技有限公司具有多年丰富的燃气采暖炉设计和制造经验,可以满足国内外不同客 户的需求。

Zhongshan Calorie Heat Energy Technological Co., Ltd has many years' experience in designing and manufacturing gas heating boilers which can meet different clients' requirements.

全自动实用太阳能燃气互补壁挂炉





中山市卡洛力热能科技有限公司 ZHONGSHAN CALORIE HEAT ENERGY TECHNOLOGICAL CO.,LTD.

地址:广东省中山市东凤镇同安大道西 Company address:Tongan Road west,DongFeng Town,ZhongShan,GuangDong,China. 电话(Tel): 0760-22781718(总机): 22781762(外销): 22781780(内销) 传真(Fax): 0760-22781719 http://www.zskili.cn